



SYSTEM MODEL		GLS-1201-HH
	Design Flow Rate, GPM	4200@40 TDH
Item 1	Separator Model	CS-12T-FLG Carbon Steel, Powder Coated
Item 2	Frame Construction	Carbon Steel, Powder Coated
Item 3	Pipe Assembly	Carbon Steel, Rust Inhibitor Primer with Enamel Finish
<b>MOTOR 460 VAC TEFC</b>		
	Horsepower	60 hp
Item 4	Approximate Amps @ 460V	77 amps
	RPM	875
<b>PUMP</b>		
	Pump Casing	Cast Iron
Item 5	Pump Impeller	304 Stainless Steel
	Std. Mechanical Seal	EPDM/Carbon/Silicon Carbide
<b>Y- STRAINER (Optional)</b>		
	Body Construction	Cast Iron
Item 6	Internal Screen	1/4" Perforated 304 Stainless Steel
	Connection Type	Class 150 Flange
<b>CONTROL PANEL (UL listed and labeled, manufactured to UL-508A Std.)</b>		
	Enclosure	NEMA 4 Powder Coated, Watertight, UL listed and CSA approved
Item 7	Electrical Components	Disconnect Starter with Thermal Overload, HOA, 460/120 Transformer with Circuit Breakers, Pump "RUN" Light, Lockable Door Disconnect, Magnetic Contactor, Purge Timer, Manufactured with all UL listed & CSA approved electrical components.
<b>PURGE VALVE (Requires Power to Open and Power to Close. Must Close Manually if Open During a Power Outage)</b>		
	Actuator, Motorized	120 VAC 60Hz
Item 8	Connection Type	2" Female NPT, Ball Valve
<b>SPECIFICATIONS</b>		
	Dim "A"	109-3/8"
	Dim "B"	68-1/2"
	Dim "C"	106"
	Max. Inlet P.S.I.	100
	Max. Operating P.S.I.	150
	Max. Operating Temp.	100°F
	Inlet	14" FLG
	Outlet	12" FLG
	Shipping Weight	5500 Lbs

\* Component Arrangement May Vary from Drawing

Note: Dimensions are approximate and are for reference only. Dimensions subject to change without notice. Weights are approximate.

**MAKING WATER WORK**

2801 Barranca Parkway  
Irvine, CA 92606 | 386.663.3370 | info@griswoldwatersystems.com

GWS-1176 REV A  
GLS-1201 HH

GriswoldWaterSystems.com