



This drawing is for spatial consideration only. Do not pre-plumb to these dimensions.

**NOTES**

- 1. INLET IS 2" PIPE (NPT THREAD)
- 2. OUTLET IS 2" PIPE (NPT THREAD)
- 3. PURGE OUTLET IS 1"
- 4. MAXIMUM PRESSURE: 150 psi (10.3 bar)
- 5. SPECIFIED FLOWRATE OF 115 gpm
- 6. MAXIMUM TEMPERATURE: 120°F (48.9°C)
- 7. FLOODED SUCTION REQUIRED
- 8. INLET/OUTLET VALVE KIT OPTIONAL

**COMPONENT LIST**

- ① ELECTRICAL CONTROL PANEL
- ② PUMP
- ③ SEPARATOR: CS-2T-THD
- ④ BASKET STRAINER OPTIONAL-SHIPED LOOSE
- ⑤ PURGE VALVE

THIS DOCUMENT MAY CONTAIN PROPRIETARY INFORMATION. IT MAY NOT BE REPRODUCED OR TRANSFERRED TO OTHERS OR USED FOR MANUFACTURING OR ANY OTHER PURPOSE WITHOUT PRIOR WRITTEN PERMISSION.		<b>GRISWOLD WATER SYSTEMS</b>			
		1597 INDUSTRIAL DRIVE, NEW SMYRNA BEACH, FL 32168			
		<b>GLS-201 HH</b>			
DRAWN	-	DATE: 3-7-11	-	MATERIAL:	CARBON STEEL
APPRD	-			DRAWING NO.	-
		WEIGHT: 420 lbs. (191 kg.)	SCALE	-	SIZE
					A
					REV.
					-
					SHEET 1 OF 1