

For Orders, Please contact:

GRISWOLD WATER SYSTEMS PROFESSIONAL SERIES CHEMICAL BYPASS FEEDER CATALOG



Griswold Water Systems Professional Chemical Bypass Feeders have a reputation for their rugged, heavy gauge steel construction and ergonomic design that allows for quickly and safely dosing your water system. Our Domed Bottom (DB) grooved end closure potfeeders meet an industry leading 350 psi at 250 °F rating. Our Elite series is designed for even more extreme conditions up to 600 psi at 650 °F. A full line of accessories enables you to convert your potfeeder into an effective filter.

FLAT BOTTOM (FB) PROFESSIONAL SERIES

Rugged design with flat bottom for floor or pedestal mounting • Three access ports – two on neck, one on side base • Safety bar closure standard • Powder coated external
• 320 psi at 250 °F rating



Item Number	Description	Old Model #	Price
FB-2-SB-CS-Z	2 gal. FB series potfeeder, safety bar closure, carbon steel body	FB-2	
FB-5-SB-CS-Z	5 gal. FB series potfeeder, safety bar closure, carbon steel body	FB-5	
FB-12-SB-CS-Z	12 gal. FB series potfeeder, safety bar closure, carbon steel body	FB-12	

DOMED BOTTOM (DB) PROFESSIONAL SERIES

Our welded leg mounted potfeeders provide easy access • Four access points – two on neck, one on side base, and one under-mounted port for easy drainage • Powder coated external • Safety bar or Victaulic cap closure options • Safety bar closure potfeeder rated for 320 psi at 250 °F • Victaulic cap closure potfeeder rated for 350 psi at 250 °F



Item Number	Description	Old Model #	Price
DB-2-SB-CS-Z	2 gal. DB series potfeeder, safety bar closure, carbon steel body	CF-2	
DB-5-SB-CS-Z	5 gal. DB series potfeeder, safety bar closure, carbon steel body	CF-5	
DB-12-SB-CS-Z	12 gal. DB series potfeeder, safety bar closure, carbon steel body	N/A	
DB-2-GE-CS-Z-230	2 gal. DB series potfeeder, grooved end/cap closure, carbon steel body, temp rated 230°F	N/A	
DB-2-GE-CS-Z-250	2 gal. DB series potfeeder, grooved end/cap closure, carbon steel body, temp rated 250°F	N/A	
DB-5-GE-CS-Z-230	5 gal. DB series potfeeder, grooved end/cap closure, carbon steel body, temp rated 230°F	N/A	
DB-5-GE-CS-Z-250	5 gal. DB series potfeeder, grooved end/cap closure, carbon steel body, temp rated 250°F	N/A	
DB-12-GE-CS-Z-230	12 gal. DB series potfeeder, grooved end/cap closure, carbon steel body, temp rated 230°F	N/A	
DB-12-GE-CS-Z-250	12 gal. DB series potfeeder, grooved end/cap closure, carbon steel body, temp rated 250°F	N/A	

DOMED BOTTOM ASME PROFESSIONAL SERIES

Same, well-designed product as our standard Domed Bottom feeders with ASME pressure vessel certification and stamped nameplate • Victaulic cap only rated for 600 psi at 250°F



Item Number	Description	Old Model #	Price
DB-2-GE-CS-A-230	2 gal. DB series potfeeder, grooved end/cap closure, carbon steel, ASME stamped, temp rated 230°F	CBF-2-GE	
DB-2-GE-CS-A-250	2 gal. DB series potfeeder, grooved end/cap closure, carbon steel, ASME stamped, temp rated 250°F	N/A	
DB-5-GE-CS-A-230	5 gal. DB series potfeeder, grooved end/cap closure, carbon steel, ASME stamped, temp rated 230°F	CBF-5-GE	
DB-5-GE-CS-A-250	5 gal. DB series potfeeder, grooved end/cap closure, carbon steel, ASME stamped, temp rated 250°F	N/A	
DB-12-GE-CS-A-230	12 gal. DB series potfeeder, grooved end/cap closure, carbon steel, ASME stamped, temp rated 230°F	CBF-10-GE	
DB-12-GE-CS-A-250	12 gal. DB series potfeeder, grooved end/cap closure, carbon steel, ASME stamped, temp rated 250°F	N/A	

ELITE PROFESSIONAL SERIES

Our Elite series includes a full range of stainless steel potfeeders in various grades, dual stainless/ASME stamped models, and a range of high pressure, temperature threaded closure feeders for applications up to 600 psi at 650 °F • Please contact your local reseller or our factory for specifications and current pricing • (Elite Series not pictured)

ACCESSORIES

We offer a complete range of interchangeable accessories for use with our potfeeder models including filter elements in a range of porosities • All Safety Bar Models are compatible with cartridge filter accessories • Please contact your local reseller if you need a different micron size



Item Number	Description	Price
CF-25-100	25 micron cartridge filter element for temp less than 100°F	
CF-25-170	25 micron cartridge filter element for temp less than 170°F	
CF-25-250	25 micron cartridge filter element for temp less than 250°F	
CF-2525-100	25 micron cartridge filter element for temp less than 100°F, qty. 25	
CF-2525-170	25 micron cartridge filter element for temp less than 170°F	
CF-2525-250	25 micron cartridge filter element for temp less than 250°F, qty. 25	
CFA	cartridge filter assembly (no filter element included) for safety bar models only	
F-75	funnel only	
FP-75	funnel and valve package. Includes one funnel and one 3/4" valve, with integral vent valve	
P-12	pedestal for FB series potfeeders, 2 and 5 gallon only	
SB-25	polyester filter bag, 25 microns	
SB-2525	polyester filter bag, 25 microns, qty 25	
SB-SS	stainless steel basket for use with filter bag	
VP-75	valve package with 3/4" NPT connections. Includes 2 valves, with integral vent valve and drain valve	

PROPOSALS & ENGINEERING

1597 INDUSTRIAL DRIVE, NEW SMYRNA BEACH, FL 32168 | T: 386.663.3370 F: 386.663.3371

CUSTOMER SERVICE & MANUFACTURING

1525 EAST 6TH STREET, CORONA, CA 92879 | T: 951.278.8992 F: 951.735.0798